

# ZAXWEL 32 Hydrostatic Level Transmitter-With Display



Application	Liquids
Measuring Range	0~350m
Process Connection	Thread, Flange
Medium Temperature	-20~85°C
Accuracy	0.1%F.S 0.2%F.S 0.5%F.S
Housing Protection	IP66
Power Supply	8-30V DC
Signal Output	4-20mA Two Wire/RS485Modbus

Specification	Code	Parameters		
Instrument Type	S	Standard		
	Z	Customized		
Process Connection	G3	Thread G <sup>3</sup> / <sub>4</sub>	H	Thread G1.0
	F15	DN40	F2	DN50
	F25	DN65	F3	DN80
	F4	DN100	F5	DN125
	F6	DN150	Z	Customized
	Output	M	4-20mA /8-30V DC	
N		RS485,MODBUS /12-30V DC		
O		4~20mA HART/12-30V DC		
Z		Customized		
Electrical Interface	M	M20*1.5		
	Z	Customized		
Probe Type	P1	304 Probe φ 28.2		
	P2	304 Probe φ 28.2 + Filter Head		
	P3	316 Probe φ 28.2		
Display	D	Yes		
	N	Na		
Measuring Range	XX	User Defined /Unit (Meter)		
Cable Length	XX	User Defined /Unit (Meter)		

