

ZAXWEL 33 Hydrostatic Level -High Temp&Corrosion



Application	Liquids
Measuring Range	0~10m
Process Connection	Thread、 Flange
Medium Temperature	-20~300°C
Accuracy	0.1%F.S 0.2%F.S 0.5%F.S
Housing Protection	IP66
Power Supply	8-30V DC
Signal Output	4-20mA Two Wire/RS485Modbus

Specification	Code	Parameters
Instrument Type	T	High Temperature
	AC	Anti-corrosive
Material	4	SS304
	6	SS316L
	P	PTFE
	Y	Special Custom
Process Connection	H	Thread G1.0
	F15	DN40
	F2	DN50
	F25	DN65
	F3	DN80
	F4	DN100
	F5	DN125
	F6	DN150
	Z	Customized
Output	M	4-20mA /8-30V DC
	N	RS485,MODBUS /12-30V DC
	O	(4~20mA HART/12-30V DC
	Z	Customized
Electrical Interface	E	M20*1.5
	Z	Customized
Probe Type	P1	304 Probe φ 28.2
	P2	316 Probe φ 28.2
	P3	Anti-Corrosive Probe
	Z	Customized
Display	D	Yes
	N	Na
Measuring Range	XX	User Defined/ Unit Meter
Calibration Range	XX	User Defined/ Unit Meter

