

Wall Mounted Ultrasonic Flowmeter





Overview

ZXDS Ultrasonic Flow Meter is a wall mounted, transit-time ultrasonic flow and BTU meter, with clamp on transducer for non-invasive liquid flow measurement. Easy to use, it is ideal for installation in existing systems when shutdowns are impractical. For BTU/Energy applications both clamp-on and insertion RTDs are available.



Applications

Widely used for water supply, non-conductive liquid such as distilled water, food oil & light oil, boiler fuel oil engine for diesel measurement, and air conditioner system to measure the flow & heat, food and beverage, pharmaceutical, ballast water, fuel consumption and other processes on-board ship.



Feature

- High Accuracy of +/-1.0% of reading
- 2 line LCD display with flowrate, totalizer
- Transducers for pipe size from 1/2" ~ 240" (DN15 ~ DN6000)
- Temperatures of up to 160°C
- Available with clamp on or insertion RTDs for BTU/Energy application
- Support SD card memory
- Configure with dual power 8~36VDC and 85~264 VAC



Specifications

Measuring Principle	Transit time ultrasonic
Pipe Size	S2 transducer: ½" ~ 4"(DN15-DN100mm) M2 transducer: 2"~ 28"(DN50-DN700mm) L2 transducer: 12"~ 240"(DN300-DN6000mm)
Pipe Material	Carbon Steel,Stainless Steel, Cast Iron, Ductile Iron, Copper,PVC,Aluminum
Display	2 line LCD with backlight
Engineering Units	Cubic Meter, Liter, US Gallon, Million US Gallon, Cubic feet, US liquid barrel, Imperial liquid barrel, Oil barrel
Time units	Second, Minute, Hour, Day
Accuracy	+/- 1 of reading (0.5 ~ 5 m/s)
Data logger	SD card optional
Repeatability	+/- 1% of reading
Communication	RS485/Modbus
Keypad	16 key with tactile action
Response Time	0-999 seconds,user chose
Flow Velocity	±32m/s
Ambient Temperature	-30°C ~ 80°C
Mounting	Wall mounted
Max.Cable Length	100 meter
Power Consumption	Less than 5W
Power Supply	24VDC and -85 ~264VAC 50/60HZ
Data Storage	Operation parameters,totalization
Output	One way 4-20mA analog, electric resistance: 0~1k, accuracy: 0.1% One way OCT pulse One way Relay
Protection	Converter and Sensor: IP65; Sensor: IP68 optional
Language	English, China, Italy, Turkey

Wall Mounted Ultrasonic Flowmeter



Standard Transducer

Flow transducer	Picture	Model	Measuring range (mm)	Temperature
Clamp on		S2 (small)	DN15-DN100	-30°C ~ 90°C
		M2 (medium)	DN50-DN700	
		L2 (large)	DN300-DN6000	
High temp. clamp on		S2-HT (small)	DN15-DN100	-30°C ~ 160°C
		M2-HT (medium)	DN50-DN700	
		L2-HT (large)	DN300-DN6000	
Insertion		TC-1 (standard)	DN50-6000	-30°C ~ 160°C
		TC-2 (extended)		
		TP-1 (parallel)	DN200-6000	
Inline		Standard	DN15-1000	-30°C ~ 160°C

Temperature transducer	Picture	Model	Measuring range	Temperature	Cut off water
Clamp on		CT-1	≥ DN50	-40°C ~ 160°C	No need
Insertion		TCT-1	≥ DN50	-40°C ~ 160°C	Need
Insertion under pressure		PCT-1	≥ DN50	-40°C ~ 160°C	No need

Wall Mounted Ultrasonic Flowmeter



Parts



Installation



Insertion Type










Clamp On Type



Pipe Type



Transducers Mounting Allocation

Piping Configuration and Transducer Position	Upstream Dimension	Downstream Dimension
	L up x Diameters	L dn x Diameters
	10D	5D
	10D	5D
	10D	5D
	12D	5D
	20D	5D
	20D	5D
	30D	5D



Model Selection

DESCRIPTION	ZXDS	XX	XX	XX	XX	XX	XX
Flowmeter Unit	Wall mounted	400F					
Transducers	Small clamp sensor, 1/2" ~ 4" (DN15 ~ DN100),(-30 ~ 90°C)		S2				
	Middle clamp sensor, 2" ~ 28" (DN50 ~ DN700),(-30 ~ 90°C)		M2				
	Large clamp sensor, 12" ~ 240" (DN300 ~ DN6000), (-30 ~ 90°C)		L2				
	High Temperature small clamp sensor, 1/2" ~ 4" (DN15 ~ DN100), (-30 ~ 160°C)		S2H				
	High Temperature middle clamp sensor, 2" ~ 28" (DN50 ~ DN700), (-30 ~ 160°C)		M2H				
	High Temperature large clamp sensor, 12" ~ 240" (DN300 ~ DN6000), (-30 ~ 160°C)		L2H				
Signal Cable Length	5m length, 2 Cables (Standard length)			S1			
	Optional cable length			O1			
Temperature sensor	Without temperature sensor				W1		
	With temperature sensor (PT100)				N1		
SD card data storage	Without SD card data storage					0	
	With SD card data storage					1	
Protection Class	IP65 Protection for transducers						ST
	IP68 Protection for transducers						IP68