

# ZAXSONIC 41 Ultrasonic Level Transmitter-Standard



Application	Liquids
Measuring Range	0~20m
Process Connection	Thread/Bracket/Flange
Process Pressure	≤0.3MPa
Accuracy	0.5%
Protection Grade	Body IP65/Probe IP68
Signal Output	4~20 mA /RS485 Modbus

Type	Code	Parameters		
Sensor Type	S	Standard		
	P	Anti-Corrosion Type		
Housing	A	Aluminium/Single Chamber		
	AD	Aluminium/Dual Chamber		
	P	Plastic		
	D	Stainless Steel		
Probe Size	G8	Thread G2.0, 5m/10m		
	M2	Thread M60, 5m/10m		
	M3	Thread M78*2/15m		
	M4	Thread M78*2/20m		
	Z	Customized		
Power Supply	A	24V DC		
	B	220V AC		
	Z	Customized		
Output Mode	2C	Two-Wire 4-20mA/No Relay		
	4M	Four-Wire 4-20mA		
	R	RS485 MODBUS-RTU		
	MR	4~20mA+RS485 MODBUS-RTU		
	Z	Customized		
Relay Output	X	No Relay		
	R2	Two Relays		
Electrical Interface	M	M20*1.5		
	N	1/2"NPT		
Calibrate Range	X	Unit: m		
Process Connection	T	Thread	F25	Flange DN65
	F3	Flange DN80	F4	Flange DN100
	B	Bracket		
Note				

