

ZAXVIB 42 Hirschmann Type



Application	Solid Particles, Powder,Liquid
Medium temp	-40~300°C
Power	3W
Time Delay	1-30s
Vibrating Frequency	300±50HZ
Output	Relay,negative,AC250V/4A,DC60V/4A Open,collector,NPN,negative 400mA Open,collector,PNP,negative 400mA
Power Supply	24V DC/220V AC
Protection	IP65



Type	Code	Parameters		
Instrument type	S	Standard		
Process Connection	G4	Thread G1.0	G3	Thread G¾ Mini Fork
	F15	Flange DN40	F2	Flange DN50
	F25	Flange DN65	F3	Flange DN80
	C8	Clamp 2.0		
	Z	Customized		
Material	4	SS304		
	6	SS316		
	P	PTFE		
Medium Temp	T1	≤80°C		
	T2	≤150°C		
	Z	Customized		
Power Supply	AD	220V AC/24V DC		
	A	220V AC		
	D	24V DC		
Output Mode	2C	Relay DPDT 5A 250VAC Max/5A 72VDC Max		
	4M	Relay SPDT 5A 250VAC/ Max 5A 60VDC Max		
	R	PNP/NPN 18-50V DC Three—Wire		
	MR	NAMUR Two-Wire		
	Z	Customized		